



**CBased Environmental
Pty Limited**
ABN 62 611 924 264



Calga Quarry

Environmental Monitoring

**Dust Deposition Gauges, Surface and Ground
Waters and Meteorological Station**

October 2017

Colin Davies BSc MEIA CENVP
Environmental Scientist
Date: 6 December 2017

Executive Summary

CBased Environmental is contracted by Hanson Quarry Products to conduct environmental monitoring at the Calga Sand Quarry.

The monitoring includes;

- Dust Deposition Gauges;
- Surface Waters;
- Groundwaters; and
- Meteorological Station.

This report was prepared by CBased Environmental and includes the following;

- Dust Deposition results for October 2017;
- Surface Water quality results for October 2017; and
- Meteorological report for October 2017.

The October 2017 dust deposition results for insoluble solids were generally low and free of major contamination. All sites, on a rolling annual average basis, are currently below the Air Quality Management Plan exceedance level of 3.7g/m².month. Results were found to be representative of dust levels as determined by the Australian Standard.

Monthly surface water samples were collected at sites A, C1, C2 and F. Sites B and D were dry at the time of sampling. The samples were collected and analysed for a monthly sampling event. Results show pH within the slightly acidic range, low Electrical Conductivity, low Total Dissolved Solids and low Total Suspended Solids. Oil and Grease was not detected at any sites in October 2017.

Bi-monthly groundwater monitoring is next scheduled for November 2017.

Data for October 2017 shows that rainfall recorded at the Calga Quarry was lower than the Gosford BOM mean rainfall and the Peats Ridge long term rainfall for October.

The rainfall comparison is provided below:

Calga Quarry	50.4 mm
BOM Peats Ridge*	NA
BOM Gosford*	79.2 mm
BOM Peats Ridge Long term mean for October*	85.3 mm

NA = Not Available

*Data sourced from Bureau of Meteorology (BOM) website (www.bom.gov.au).

Note: Differences in the daily rainfall readings between BOM and the Calga station may occur due to BOM stations reporting rainfall at 9am and the Calga station recording rainfall at midnight.

Sampling Program

Hanson Calga Quarry conducts environmental monitoring in accordance to Development Consent, OEH (EPA) licence and Environmental Management Plans. CBased Environmental are contracted to undertake dust deposition gauge, surface and groundwater and meteorological monitoring for the project. CBased Environmental commenced monitoring from the April 2006 monitoring period.

Dust deposition gauges are operated to the Australian Standard AS3580.10.1 “*Methods for sampling and analysis of ambient air method. Determination of particulates- deposited matter- gravimetric Method*”. Sampling is undertaken every 30 +/- 2 days and each gauge is analysed for insoluble solids and ash residue. The results are reported as g/m².month.

Surface waters are sampled in accordance with Australian Standards AS5667.1 “*Guidance on the design of sample programs, sampling techniques and the preservation and handling of samples*”, AS5667.6 “*Water quality sampling—guidance on sampling of rivers and streams*” and AS5667.4 “*Water quality sampling—guidance on sampling from lakes, natural and man-made*”. Surface water monitoring sites include local streams and dams. Basic analysis including pH, Electrical Conductivity, Total Suspended Solids, Total Dissolved Solids and Total Oil and Grease is conducted monthly at Sites A and F (dams) and when Sites B, C and D are flowing. Additional samples are collected when daily rainfall exceeds 50mm.

Groundwaters are sampled in accordance with Australian Standards AS5667.1 “*Guidance on the design of sample programs, sampling techniques and the preservation and handling of samples*” and AS5667.11 “*Water quality sampling—guidance on sampling of ground waters*”. Groundwater monitoring sites are sampled bi-monthly for depth and water quality. Groundwater monitoring loggers continuously record water levels in a selection of bores.

Meteorological monitoring is conducted at the quarry and displayed on the site computer with a real-time display. Metrological parameters are measured according to Australian Standard AS3580.14 “*Methods for sampling and analysis of ambient air. Meteorological monitoring for ambient air quality monitoring applications*”

The weather stations have the following sensor configuration;

- Air temperature
- Humidity
- Rainfall
- Atmospheric pressure
- Evaporation
- Solar radiation
- Wind speed
- Wind direction

CBased Environmental continued to operate the monitoring equipment and utilise site collections at their existing locations.

The locations of monitoring points are provided in **Figure 1**.




Figure 1: Hanson Calga Quarry environmental monitoring locations

2.0 Monthly Results

2.1 Dust Deposition Gauges

Table 1 displays the results for October 2017 and the project 12-month rolling average. Results are in g/m².month.

Table 1: Dust Deposition results: 3 October 2017 – 2 November 2017 (29 days)

Site	Monthly Insoluble Solids (g/m ² .month)	Monthly Ash Residue (g/m ² .month)	Monthly Combustible Matter (g/m ² .month)	Monthly Ash Residue/ Insoluble Solids %	Rolling Annual Average Insoluble Solids (g/m ² .month)
CD1	2.4	2.1	0.3	88	3.0
CD2c	1.2	0.9	0.3	75	1.0
CD3	1.7	0.7	1.0	41	1.2
CD4	0.2	<0.1	0.2	50	0.6
CD5	0.5	0.2	0.3	40	0.7
CD6	1.0	0.5	0.5	50	0.8


Insoluble Solids marked with an * indicate an excessively contaminated gauge. Contamination can include bird droppings, vegetation (such as plant matter, algae, pollen and seeds) and insects. Results in bold indicate insoluble solids levels above 3.7 g/m².month; the Development Consent's annual average amenity criteria at residential locations. The current rolling annual average is calculated from November 2016 to October 2017.

NA= Not Available.

CD1 was installed on the 1 May 2006. CD2a was discontinued at the start of August 2006 due to quarry operations "mining out" the site of the gauge. The replacement gauge, Site CD2b, was located in a position adjacent to the boundary between B. Kashouli and F. & J. Gazzana in conformance with the Air Quality Management Plan. CD4 was installed on 3 October 2006, to gauge air quality impacts to the south of the site operations, as were CD5 and CD6 which were installed on the 14 December 2006. CD2b was discontinued at the end of January 2010 due to contamination of the gauge by non-quarry related vehicle movements on a track adjacent to the gauge. The replacement gauge, CD2c, was located on a rehabilitated section of land between the extraction area and adjacent resident.

Dust deposition charts for all dust gauge sites appear in **Figure 2** below. The laboratory analysis is provided in **Appendix 1**.

Figure 2: Dust Deposition Charts



2.2 Surface Water Monitoring

Monthly surface water monitoring was conducted on the 2 November 2017 and results are listed in **Table 2**. The laboratory analysis sheets are provided in **Appendix 1**.

Table 2: Monthly surface water monitoring – October grab sample results

Site	Observed Flow Rate	Water Colour	Turbidity	pH	EC ($\mu\text{S}/\text{cm}$)	TDS (mg/L)	TSS (mg/L)	Oil and Grease (mg/L)
A	Still	Brown	Clear	6.77	96	78	8	<5
B	Dry							
C1	Dam	Clear	Clear	7.34	100	77	15	<5
C2	Steady	Clear	Clear	6.7	100	67	6	<5
D	Dry							
F	Still	Clear	Clear	5.44	93	68	<5	<5

Samples were collected at sites A, C1, C2 and F. Sites B and D were dry at the time of sampling. The samples were collected and analysed for a monthly sampling event. Results show pH within the slightly acidic range, low Electrical Conductivity, low Total Dissolved Solids and low Total Suspended Solids. Oil and Grease was not detected at any sites in October 2017.

2.2.1 Non-Routine Surface Water Sampling

No non-routine sampling was undertaken during October 2017.

2.3 Groundwater Monitoring

Bi-monthly groundwater monitoring is next scheduled for November 2017.

2.4 Meteorological Monitoring

The Calga Quarry weather station data recovery in October 2017 was approximately 94%. No data was available from 30 October – 31 October 2017.

The weather station data follows and includes;

- Monthly data numerical summary;
- Weather charts of air temperature, humidity, heat index and wind chill, atmospheric pressure, solar radiation, evapotranspiration, rain, wind speed and data reception; and
- Wind rose (frequency distribution diagram of wind speed and direction).

Monthly weather statistics from the nearby Bureau of Meteorology (BOM) at Peats Ridge station are no longer available. However, the long-term rainfall mean is available via a link on the Gosford BOM Daily Weather Observation page.

Data for October 2017 shows that rainfall recorded at the Calga Quarry was lower than the Gosford BOM mean rainfall and the Peats Ridge long term rainfall for October.

The rainfall comparison is provided below:

Calga Quarry	50.4 mm
BOM Peats Ridge*	NA
BOM Gosford*	79.2 mm
BOM Peats Ridge Long term mean for October*	85.3 mm

NA = Not Available

^Rain data not based on a full set of data.

*Data sourced from Bureau of Meteorology (BOM) website (www.bom.gov.au).




2.4.1 Monthly Meteorological Data Summary




Summary Oct-17 Hanson - Calga

Date	Min Temp	Av Temp	Max Temp	Min %RH	Av %RH	Max %RH	RAIN mm	ET mm	Min WS	Av WS	Max WS	Min wind chill	Max Heat index	Min Atm P	Av Atm P	Max Atm P	Min Solar Rad	Av Solar Rad	Max Solar Rad	Min Data %	Av data %	Max Data %
1/10/2017	8.7	15.3	24.8	22.0	65.6	95.0	0.0	4.9	0.0	1.7	8	8.7	24.2	1018.7	1021.7	1023.5	0.0	271.1	897.0	100	100.0	100.0
2/10/2017	9.7	16.8	26.2	34.0	72.2	93.0	0.0	4.2	0.0	2.3	10.7	9.7	25.9	1020.9	1023.4	1025.6	0.0	227.2	1002.0	99.1	100.0	100.0
3/10/2017	14.5	18.1	25.2	53.0	79.2	93.0	0.0	2.8	0.0	1.7	8.5	14.5	25.7	1019.7	1022.3	1024.8	0.0	146.8	757.0	81.5	98.0	100.0
4/10/2017	12.5	17.2	23.8	58.0	85.6	96.0	0.0	2.8	0.0	1.3	8.5	12.6	24.4	1019.6	1021.3	1023.3	0.0	169.7	846.0	75.7	97.7	100.0
5/10/2017	15.7	20.7	28.9	48.0	76.5	94.0	0.0	4.2	0.0	2.1	8.5	15.7	30.5	1011.0	1016.2	1021.4	0.0	222.8	924.0	26.8	91.2	100.0
6/10/2017	14.7	17.1	20.5	61.0	76.6	91.0	0.0	2.0	0.0	1.4	8.9	14.7	20.4	1010.8	1016.2	1023.3	0.0	99.4	678.0	84.9	97.8	100.0
7/10/2017	11.6	15.3	20.4	46.0	71.0	92.0	0.0	3.6	0.0	1.9	8.0	11.6	20.0	1021.7	1023.2	1024.9	0.0	196.8	987.0	78.5	96.5	100.0
8/10/2017	10.2	15.7	21.6	62.0	85.3	95.0	0.8	1.8	0.0	0.9	6.7	10.2	22.0	1013.9	1018.8	1023.4	0.0	116.1	708.0	92.3	98.4	100.0
9/10/2017	16.2	23.0	31.9	27.0	63.7	92.0	0.0	5.3	0.0	2.4	10.3	16.2	32.1	1006.5	1011.0	1014.9	0.0	239.2	956.0	67.1	96.7	100.0
10/10/2017	15.0	17.3	20.0	70.0	82.5	93.0	0.4	1.6	0.0	2.1	7.6	15.0	20.6	1015.0	1017.8	1019.9	0.0	74.4	334.0	71.4	92.5	100.0
11/10/2017	16.3	20.2	26.7	65.0	86.1	95.0	1.2	2.8	0.0	2.6	8.0	15.9	28.1	1009.1	1014.9	1019.7	0.0	145.5	871.0	86.2	98.3	100.0
12/10/2017	15.3	22.2	30.2	16.0	63.4	92.0	0.2	6.3	0.0	2.9	12.1	15.3	28.6	1007.4	1011.8	1018.6	0.0	277.2	1010.0	69.8	96.2	100.0
13/10/2017	13.3	18.3	24.3	51.0	80.0	96.0	0.2	3.7	0.0	2.1	10.3	13.4	24.8	1015.1	1017.9	1020.0	0.0	187.9	911.0	83.7	96.1	100.0
14/10/2017	14.1	15.3	17.8	85.0	92.3	96.0	8.4	0.8	0.0	1.8	8.9	14.1	18.3	1019.2	1023.6	1026.4	0.0	42.5	196.0	88.6	99.5	100.0
15/10/2017	14.2	16.0	19.2	81.0	92.9	97.0	6.0	1.7	0.0	1.3	7.6	14.2	20.3	1024.6	1026.1	1027.9	0.0	98.7	576.0	87.1	96.3	100.0
16/10/2017	12.2	16.6	22.3	56.0	82.3	97.0	0.2	3.6	0.0	1.8	8.9	12.2	22.9	1026.6	1028.2	1029.6	0.0	200.3	1078.0	85.2	97.0	100.0
17/10/2017	13.4	17.6	22.7	56.0	78.8	94.0	0.0	3.9	0.0	2.9	11.6	13.4	22.9	1027.4	1028.6	1029.9	0.0	191.1	1100.0	83.1	96.3	100.0
18/10/2017	15.2	18.6	23.2	60.0	79.8	94.0	0.0	4.4	0.0	4.0	12.5	15.2	23.8	1026.0	1028.0	1029.8	0.0	202.5	996.0	73.8	93.6	100.0
19/10/2017	13.9	20.8	29.6	37.0	70.1	92.0	0.0	5.9	0.0	2.5	10.3	13.9	30.1	1018.8	1022.8	1027.3	0.0	294.5	935.0	76.9	91.6	100.0
20/10/2017	13.3	16.0	19.3	84.0	91.8	96.0	16.0	0.7	0.0	1.8	10.3	12.4	20.2	1017.6	1021.3	1025.1	0.0	29.5	173.0	74.3	90.9	98.0
21/10/2017	10.5	14.1	17.3	61.0	77.7	94.0	0.0	3.2	0.0	2.2	8.9	10.5	17.4	1018.7	1021.5	1024.6	0.0	188.3	839.0	78.7	89.9	97.7
22/10/2017	8.8	14.3	21.7	49.0	82.4	96.0	12.4	2.9	0.0	1.5	7.6	8.8	21.3	1013.1	1015.9	1018.5	0.0	184.8	1175.0	79.5	86.7	92.1
23/10/2017	11.3	15.5	21.0	58.0	82.2	96.0	0.0	3.7	0.0	1.8	8.5	11.4	20.8	1017.1	1018.8	1020.9	0.0	230.8	1150.0	81.8	94.8	100.0
24/10/2017	11.7	19.0	29.5	28.0	69.1	95.0	0.2	5.8	0.0	2.0	10.3	11.8	28.6	1014.6	1017.9	1020.6	0.0	310.1	989.0	85.8	96.3	100.0
25/10/2017	16.4	22.8	30.6	26.0	51.3	88.0	0.0	5.6	0.0	2.2	9.4	16.4	29.5	1008.3	1012.2	1015.8	0.0	223.3	967.0	72.9	91.1	100.0
26/10/2017	15.4	19.1	24.1	67.0	84.5	93.0	1.6	2.8	0.4	2.2	14.8	14.1	25.2	1002.0	1006.3	1011.3	0.0	155.0	857.0	75.4	93.4	100.0
27/10/2017	13.4	17.6	22.3	69.0	86.7	95.0	2.8	2.5	0.0	2.4	11.2	12.1	23.1	1005.5	1009.7	1013.6	0.0	142.4	1025.0	76.0	96.0	100.0
28/10/2017	15.1	21.1	29.1	39.0	76.2	96.0	0.0	4.5	0.0	1.4	6.7	15.2	29.9	1007.9	1010.8	1013.1	0.0	259.5	958.0	74.3	92.8	98.0
29/10/2017	20.0	24.7	32.6	32.0	52.1	71.0	0.0	6.8	0.0	2.7	10.7	20.1	32.8	1004.6	1007.0	1009.7	0.0	297.7	1144.0	88.0	92.6	96.2
30/10/2017																						
31/10/2017																						
Monthly	8.7	18.1	32.6	16	77	97	50.4	104.9	0	2.1	14.8	8.7	32.8	1002	1018.5	1029.9	0	187.1	1175	26.8	95.1	100


No data

2.4.2 Monthly Weather Charts







Hanson Calga Quarry - October 2017
Rainfall



Hanson Calga Quarry - October 2017
Evapotranspiration




Hanson Calga Quarry - October 2017
Data Reception



2.4.3 Monthly Windrose Plot

Frequency plot of the average wind speed and average direction over each 15-minute sampling period. Wind is considered to be calm when at less than a 15-minute average of 1m/s.

00:15, 1 October 2017 – 08:15, 30 October 2017



The predominant winds were from the ENE, with most frequent, strongest winds also from the ENE. The maximum wind speed was 14.8 m/s from the W.

Appendix 1

Field Sheets

Chain of Custody

Laboratory Certificates

DEPOSITIONAL DUST MONITORING

Client: **Hanson Calga Quarry**

Date Installed: 3.10.17

Collection Start Time: 12.30 .

Sampled By: Laesaking
Jim Peterson

Date Collected: 2-11-17

Collection Stop Time: 1:45

Sampling ID:

[illegible]

Turbidity: C=Clear, S= Slight, T=Turbid (CIRCLE)

Colour: C=Clear, O=Orange, Bn=Brown, Gn=Green, Gy = Grey (CIRCLE)

Report broken funnels and replacement diameters

Signed: afloson

CERTIFICATE OF ANALYSIS

Work Order : **EN1704505**
Client : **CBASED ENVIRONMENTAL PTY LTD**
Contact : **MS RENAE MIKKA**
Address : **47 BOOMERANG ST**
CESSNOCK NSW, AUSTRALIA 2325
Telephone : **+61 49904443**
Project : **Hanson Calga Dusts**
Order number : **----**
C-O-C number : **----**
Sampler : **CARBON BASED ENVIRONMENTAL PTY LTD**
Site : **----**
Quote number : **SYBQ/222/16 and PLANNED EVENTS**
No. of samples received : **6**
No. of samples analysed : **6**

Page : 1 of 4
Laboratory : Environmental Division Newcastle
Contact : **----**
Address : **5/585 Maitland Road Mayfield West NSW Australia 2304**
Telephone : **+61 2 4014 2500**
Date Samples Received : **02-Nov-2017 15:00**
Date Analysis Commenced : **03-Nov-2017**
Issue Date : **09-Nov-2017 18:36**



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Dianne Blane	Laboratory Coordinator (2IC)	Newcastle - Inorganics, Mayfield West, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

Ø = ALS is not NATA accredited for these tests.

~ = Indicates an estimated value.

- Analysis as per AS3580.10.1-2016. Samples passed through a 1mm sieve prior to analysis. NATA accreditation does not apply for results reported in g/m².mth as sampling data was provided by the client.



Analytical Results

Sub-Matrix: **DEPOSITIONAL DUST**
 (Matrix: **AIR**)

Client sample ID

				CD1 03/10/17-02/11/17	CD2c 03/10/17-02/11/17	CD3 03/10/17-02/11/17	CD4 03/10/17-02/11/17	CD5 03/10/17-02/11/17
Client sampling date / time				02-Nov-2017 00:00	02-Nov-2017 00:00	02-Nov-2017 00:00	02-Nov-2017 00:00	02-Nov-2017 00:00
Compound	CAS Number	LOR	Unit	EN1704505-001	EN1704505-002	EN1704505-003	EN1704505-004	EN1704505-005
				Result	Result	Result	Result	Result
EA120: Ash Content								
Ash Content	----	0.1	g/m ² .month	2.1	0.9	0.7	<0.1	0.2
Ash Content (mg)	----	1	mg	37	16	12	<1	4
EA125: Combustible Matter								
Combustible Matter	----	0.1	g/m ² .month	0.3	0.3	1.0	0.2	0.3
Combustible Matter (mg)	----	1	mg	5	5	18	3	4
EA141: Total Insoluble Matter								
Total Insoluble Matter	----	0.1	g/m ² .month	2.4	1.2	1.7	0.2	0.5
Total Insoluble Matter (mg)	----	1	mg	42	21	30	3	8



Analytical Results

Sub-Matrix: **DEPOSITIONAL DUST**
 (Matrix: **AIR**)

Client sample ID

				CD6	----	----	----	----
				03/10/17-02/11/17	----	----	----	----
				Client sampling date / time	02-Nov-2017 00:00	----	----	----
Compound	CAS Number	LOR	Unit	EN1704505-006	-----	-----	-----	-----
				Result	----	----	----	----
EA120: Ash Content								
Ash Content	----	0.1	g/m ² .month	0.5	----	----	----	----
Ash Content (mg)	----	1	mg	8	----	----	----	----
EA125: Combustible Matter								
Combustible Matter	----	0.1	g/m ² .month	0.5	----	----	----	----
Combustible Matter (mg)	----	1	mg	9	----	----	----	----
EA141: Total Insoluble Matter								
Total Insoluble Matter	----	0.1	g/m ² .month	1.0	----	----	----	----
Total Insoluble Matter (mg)	----	1	mg	17	----	----	----	----



Date: 2-11-17

Todays Collection	
Time Start:	11:50
Time Finish:	1:35

Client :
Project :

Hanson Calga

SURFACE WATERS

Site	Flow Rate	Odour	Sampling Time	Bottles	Water Turbidity	Water Colour	Comments
A	Still	Nil	12:20	1x 250ml GP, 1x 500mL GP, 1x PG	(C)ST	CLO(O)BG	
B			11:50	1x 250ml GP, 1x 500mL GP, 1x PG	CST	CLO(O)BG	DRY
C1	Dam	Nil	1:30	1x 250ml GP, 1x 500mL GP, 1x PG	(C)ST	(C)LO(O)BG	
C2	Steady	Nil	1:35	1x 250ml GP, 1x 500mL GP, 1x PG	(C)ST	(C)LO(O)BG	
D			1:10	1x 250ml GP, 1x 500mL GP, 1x PG	CST	CLO(O)BG	DRY
F	Still	Nil	12:00	1x 250ml GP, 1x 500mL GP, 1x PG	(C)ST	(C)LO(O)BG	
					CST	CLO(O)BG	
					CST	CLO(O)BG	
					CST	CLO(O)BG	
					CST	CLO(O)BG	
					CST	CLO(O)BG	

Turbidity: C=Clear, S= Slight, T=Turbid (CIRCLE)

Colour: C=Clear, LO=Light Orange, O=Orange, B=Brown, G=Green (CIRCLE)

Signed:

Sampled by:

Leesa King
Jru Peterson

CERTIFICATE OF ANALYSIS

Work Order : **ES1727463**
Client : **CBASED ENVIRONMENTAL PTY LTD**
Contact : All Deliverables
Address : 47 BOOMERANG ST
 CESSNOCK NSW, AUSTRALIA 2325
Telephone : +61 02 6571 3334
Project : HANSON QUARRY SW
Order number : ----
C-O-C number : ----
Sampler : CARBON BASED ENVIRONMENTAL PTY LTD
Site :
Quote number : SYBQ/222/16 and PLANNED EVENTS
No. of samples received : 4
No. of samples analysed : 4

Page : 1 of 2
Laboratory : Environmental Division Sydney
Contact : Customer Services ES
Address : 277-289 Woodpark Road Smithfield NSW Australia 2164
Telephone : +61-2-8784 8555
Date Samples Received : 02-Nov-2017 15:01
Date Analysis Commenced : 02-Nov-2017
Issue Date : 08-Nov-2017 12:55



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

<i>Signatories</i>	<i>Position</i>	<i>Accreditation Category</i>
Ankit Joshi	Inorganic Chemist	Sydney Inorganics, Smithfield, NSW
Neil Martin	Team Leader - Chemistry	Chemistry, Newcastle West, NSW



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.
 LOR = Limit of reporting
 ^ = This result is computed from individual analyte detections at or above the level of reporting
 Ø = ALS is not NATA accredited for these tests.
 ~ = Indicates an estimated value.

- TDS by method EA-015 may bias high for various samples due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.

Analytical Results

Sub-Matrix: **WATER**
 (Matrix: **WATER**)

Client sample ID

				A	C1	C2	F	----
Client sampling date / time				02-Nov-2017 12:20	02-Nov-2017 13:30	02-Nov-2017 13:35	02-Nov-2017 12:00	----
Compound	CAS Number	LOR	Unit	ES1727463-001	ES1727463-002	ES1727463-003	ES1727463-004	-----
				Result	Result	Result	Result	----
EA005: pH								
pH Value	----	0.01	pH Unit	6.77	7.34	6.70	5.44	----
EA010P: Conductivity by PC Titrator								
Electrical Conductivity @ 25°C	----	1	µS/cm	96	100	100	93	----
EA015: Total Dissolved Solids dried at 180 ± 5 °C								
Total Dissolved Solids @180°C	----	10	mg/L	78	77	67	68	----
EA025: Total Suspended Solids dried at 104 ± 2°C								
Suspended Solids (SS)	----	5	mg/L	8	15	6	<5	----
EP020: Oil and Grease (O&G)								
Oil & Grease	----	5	mg/L	<5	<5	<5	<5	----