



Carbon Based Environmental
Pty Limited
ABN 74 102 920 285

Rocla Quarry Products
Calga Quarry

Environmental Monitoring

Dust Deposition Gauges, Surface and Ground
Waters and Meteorological Station

October 2015

A handwritten signature in black ink, appearing to read 'Colin Davies'.

Colin Davies BSc MEIA CENVP
Environmental Scientist
Date: 27 November 2015

Executive Summary

Carbon Based Environmental is contracted by Rocla Quarry Products to conduct environmental monitoring at the Calga Sand Quarry.

The monitoring includes;

- Dust Deposition Gauges;
- Surface Waters;
- Groundwaters; and
- Meteorological Station.

This report was prepared by Carbon Based Environmental and includes the following;

- Dust Deposition results for October 2015;
- Surface Water quality results for October 2015; and
- Meteorological report for October 2015.

The October 2015 dust deposition results for insoluble solids were generally low and free of major contamination. All sites, on a rolling annual average basis, are currently below the Air Quality Management Plan exceedance level of 3.7g/m².month. Results were found to be representative of dust levels as determined by the Australian Standard.

Surface water samples were collected on 2 November 2015 at sites A, D and F. Site B had no flow and Site C was inaccessible and was unable to be sampled this month. The samples were collected and analysed for a monthly sampling event. Results show pH within the slightly acidic range, low Electrical Conductivity, low Total Dissolved Solids and low Total Suspended Solids. Oil and Grease was not detected at any site in October 2015.

Bi-monthly groundwaters were sampled in September and are next scheduled for sampling in November 2015.

Data for September 2015 shows that rainfall recorded at the Rocla Calga Quarry was higher than the Gosford BOM and similar to the Peats Ridge long term, mean rainfall for September 2015.

The rainfall comparison is provided below:

Rocla Calga Quarry	49.7 mm
BOM Peats Ridge*	NA
BOM Gosford*	36.4 mm
BOM Peats Ridge Long term mean for October*	85.3 mm

*Data sourced from Bureau of Meteorology (BOM) website (www.bom.gov.au). No data was available from the BOM Peats Ridge station for October 2015

Note: Differences in the daily rainfall readings between BOM and the Rocla station may occur due to BOM stations reporting rainfall at 9am and the Rocla station recording rainfall at midnight.

Sampling Program

Rocla Calga Quarry conducts environmental monitoring in accordance to Development Consent, OEH (EPA) licence and Environmental Management Plans. Carbon Based Environmental are contracted to undertake dust deposition gauge, surface and groundwater and meteorological monitoring for the project. Carbon Based Environmental commenced monitoring from the April 2006 monitoring period.

Dust deposition gauges are operated to the Australian Standard [AS3580.10.1](#) “Methods for Sampling and Analysis of Ambient Air Method 10.1 Determination of Particulates—Deposited Matter—Gravimetric Method”. Sampling is undertaken every 30 +/- 2 days and each gauge is analysed for insoluble solids and ash residue. The results are reported as g/m².month.

Surface waters are sampled in accordance with Australian Standards [AS5667.1](#) “Guidance on the Design of Sample Programs, Sampling Techniques and the Preservation and Handling of Samples”, [AS5667.6](#) “Water Quality Sampling—Guidance on sampling of rivers and streams” and [AS5667.4](#) “Water Quality Sampling—Guidance on sampling from lakes, natural and man-made”. Surface water monitoring sites include local streams and dams. Basic analysis including pH, Electrical Conductivity, Total Suspended Solids, Total Dissolved Solids and Total Oil and Grease is conducted monthly at Sites A and F (dams) and when Sites B, C and D are flowing. Additional samples are collected when daily rainfall exceeds 50mm.

Groundwaters are sampled in accordance with Australian Standards [AS5667.1](#) “Guidance on the Design of Sample Programs, Sampling Techniques and the Preservation and Handling of Samples” and [AS5667.11](#) “Water Quality Sampling—Guidance on sampling of ground waters”. Groundwater monitoring sites are sampled bi-monthly for depth and water quality. Groundwater monitoring loggers continuously record water levels in a selection of bores.

Meteorological monitoring is conducted at the quarry and displayed on the site computer with a real time display. Wind parameters are measured according to Australian Standard [AS 2923](#) “Ambient Air— Guide for Measurement of Horizontal Wind for Air Quality Applications”.

The weather stations have the following sensor configuration;

Air temperature

- Humidity
- Rainfall
- Atmospheric pressure
- Evaporation
- Solar radiation
- Wind speed
- Wind direction

Carbon Based Environmental continued to operate the monitoring equipment and utilise site collections at their existing locations.

The locations of monitoring points are provided in **Figure 1**.




Figure 1: Rocla Calga Quarry environmental monitoring locations

2.0 Monthly Results

2.1 Dust Deposition Gauges

Table 1 displays the results for October 2015 and the project 12 month rolling average. Results are in g/m².month.

Table 1: Dust Deposition results: 2 October 2015 – 2 November 2015 (30 days)

Site	Monthly Insoluble Solids g/m ² .month	Monthly Ash Residue g/m ² .month	Monthly Combustible Matter g/m ² .month	Monthly Ash Residue/ Insoluble Solids %	Rolling Annual Average Insoluble Solids g/m ² .month
CD1	1.6	1.2	0.4	75	1.2
CD2c	0.9	0.5	0.4	56	1.4
CD3	0.8	0.4	0.4	50	1.0
CD4	0.4	0.2	0.2	50	0.7
CD5	0.5	0.3	0.2	60	0.6
CD6	0.5	0.3	0.2	60	0.7


Insoluble Solids marked with an * indicate an excessively contaminated gauge. Contamination can include bird droppings, vegetation (such as plant matter, algae, pollen and seeds) and insects. Results in bold indicate insoluble solids levels above 3.7 g/m².month; the Development Consent's annual average amenity criteria at residential locations. The current rolling annual average is calculated from September 2014 to August 2015.

NA= Not Available.

CD1 was installed on the 1 May 2006. CD2a was discontinued at the start of August 2006 due to quarry operations "mining out" the site of the gauge. The replacement gauge, Site CD2b, was located in a position adjacent to the boundary between B. Kashouli and F. & J. Gazzana in conformance with the Air Quality Management Plan. CD4 was installed on 3 October 2006, to gauge air quality impacts to the south of the site operations, as were CD5 and CD6 which were installed on the 14 December 2006. CD2b was discontinued at the end of January 2010 due to contamination of the gauge by non-quarry related vehicle movements on a track adjacent to the gauge. The replacement gauge, CD2c, was located on a rehabilitated section of land between the extraction area and adjacent resident.

Dust deposition charts for all dust gauge sites appear in **Figure 2** below. The laboratory analysis is provided in **Appendix 1**.

Figure 2: Dust Deposition Charts



2.2 Surface Water Monitoring

Monthly surface water monitoring was conducted on the 2 November 2015 and results are listed in **Table 2**. The laboratory analysis sheets are provided in **Appendix 1**.

Table 2: Monthly surface water monitoring – October grab sample results

Site	Observed Flow Rate	Water Colour	Turbidity	pH	EC (µS/cm)	TDS (mg/L)	TSS (mg/L)	Oil and Grease (mg/L)
A	Dam	Clear	Slight	5.37	80	41	<5	<5
B	No Flow							
C	No Access							
D	Trickle	Brown	Slight	5.97	79	64	22	<5
F	Dam	Clear	Clear	4.93	82	49	38	<5

Samples were collected at sites A, D and F. Site B had no flow and Site C was inaccessible and was unable to be sampled this month. The samples were collected and analysed for a monthly sampling event. Results show pH within the slightly acidic range, low Electrical Conductivity, low Total Dissolved Solids and low Total Suspended Solids. Oil and Grease was not detected at any site in October 2015.

2.2.1 Non-Routine Surface Water Sampling

No non routine sampling was undertaken during October 2015.

2.3 Groundwater Monitoring

Bi-monthly groundwater monitoring is next scheduled for November 2015.

2.4 Meteorological Monitoring

The Rocla Calga Quarry weather station data recovery in October 2015 was approximately 100%.

The weather station data follows and includes;

- Monthly data numerical summary;
- Weather charts of air temperature, humidity, heat index and wind chill, atmospheric pressure, solar radiation, evapotranspiration, rain, wind speed and data reception; and
- Wind rose (frequency distribution diagram of wind speed and direction).

Monthly weather statistics from the nearby Bureau of Meteorology (BOM) at Peats Ridge station are no longer available. However, the long term rainfall mean is available via a link on the Gosford BOM Daily Weather Observation page.

Data for October 2015 shows that rainfall recorded at the Rocla Calga Quarry was higher than the Gosford BOM however significantly below the Peats Ridge long term, mean rainfall for October 2015.

The rainfall comparison is provided below:

Rocla Calga Quarry	49.7 mm
BOM Peats Ridge*	NA
BOM Gosford*	36.4 mm
BOM Peats Ridge Long term mean for October*	85.3 mm




NA = Not Available




*Data sourced from Bureau of Meteorology (BOM) website (www.bom.gov.au).




2.4.1 Monthly Meteorological Data Summary

Date	Min Temp	Av Temp	Max Temp	Min %RH	Av %RH	Max %RH	RAIN mm	ET mm	Min WS	Av WS	Max WS	Min wind chill	Max Heat index	Min Atm P	Av Atm P	Max Atm P	Min Solar Rad	Av Solar Rad	Max Solar Rad	Min Data %	Av data %	Max Data %
1/10/2015	12.4	18.0	27.8	41.0	82.6	98.0	0.3	3.6	0.0	0.8	7.6	12.4	28.4	1023.1	1026.2	1029.1	0.0	238.2	870.0	91.8	96.2	98.0
2/10/2015	14.3	17.8	23.8	47.0	75.2	96.0	0.0	4.6	0.0	1.6	8.9	14.3	24.1	1029.4	1033.1	1035.0	0.0	266.5	959.0	93.3	96.6	98.0
3/10/2015	13.2	21.8	33.1	19.0	62.6	96.0	0.3	4.9	0.0	0.7	5.8	13.4	32.7	1024.7	1029.2	1033.6	0.0	271.5	908.0	88.6	96.6	98.0
4/10/2015	17.5	25.6	33.1	13.0	30.6	63.0	0.0	7.5	0.0	2.3	14.8	17.9	31.2	1022.1	1024.2	1026.0	0.0	266.1	1025.0	89.2	97.4	98.0
5/10/2015	16.2	25.5	37.5	10.0	32.5	58.0	0.0	6.1	0.0	0.8	6.7	16.3	35.2	1021.0	1023.3	1025.1	0.0	271.5	914.0	95.0	96.9	98.0
6/10/2015	16.4	26.1	36.6	12.0	38.2	67.0	0.0	6.3	0.0	0.9	8.9	16.6	35.0	1019.2	1022.1	1024.4	0.0	273.8	906.0	78.4	95.8	98.0
7/10/2015	14.4	17.4	23.9	33.0	67.3	84.0	0.0	1.7	0.0	1.1	9.8	14.4	23.3	1021.0	1031.5	1038.8	0.0	70.3	332.0	90.1	97.4	98.0
8/10/2015	14.4	15.9	18.7	60.0	76.4	92.0	0.0	1.6	0.0	1.1	7.2	14.4	18.5	1036.2	1037.8	1039.7	0.0	81.4	359.0	90.1	96.9	98.0
9/10/2015	14.3	18.2	25.1	44.0	72.3	92.0	0.0	4.6	0.0	1.5	9.8	14.3	25.4	1029.0	1032.6	1036.2	0.0	268.0	887.0	81.6	96.9	98.0
10/10/2015	13.1	18.8	28.3	42.0	77.1	97.0	0.3	3.8	0.0	0.7	7.2	13.2	28.9	1025.6	1027.9	1030.5	0.0	237.5	968.0	81.9	97.2	98.0
11/10/2015	12.8	18.0	28.2	31.0	79.7	97.0	9.1	3.4	0.0	1.0	11.2	12.9	29.7	1018.2	1021.9	1025.3	0.0	203.1	964.0	91.5	97.8	98.0
12/10/2015	14.2	20.1	30.2	30.0	74.0	95.0	2.3	4.4	0.0	1.9	10.3	14.3	29.6	1012.4	1016.4	1019.3	0.0	234.3	938.0	70.8	95.7	98.0
13/10/2015	15.7	17.5	18.7	86.0	92.0	96.0	5.1	0.9	0.0	1.2	6.3	15.8	19.6	1018.7	1023.1	1027.1	0.0	58.3	350.0	79.8	96.1	98.0
14/10/2015	13.5	18.0	24.1	55.0	84.2	99.0	0.3	4.3	0.0	2.0	8.5	13.6	24.6	1025.6	1026.9	1028.4	0.0	260.6	1189.0	82.5	96.6	98.0
15/10/2015	14.2	20.0	28.7	43.0	79.2	97.0	0.0	5.1	0.0	1.8	8.9	14.2	29.6	1021.5	1024.6	1027.4	0.0	288.3	930.0	89.8	97.3	98.0
16/10/2015	14.1	23.2	33.2	22.0	62.7	98.0	0.3	5.8	0.0	1.3	8.0	14.2	32.9	1018.6	1021.1	1023.3	0.0	294.6	949.0	44.7	93.8	98.0
17/10/2015	16.1	20.7	26.8	56.0	78.8	94.0	0.0	3.9	0.0	0.9	6.3	16.1	27.9	1020.0	1023.0	1027.2	0.0	232.6	942.0	89.2	97.6	98.0
18/10/2015	17.0	18.5	21.1	69.0	84.6	95.0	1.0	2.0	0.0	1.1	7.2	17.1	21.5	1026.7	1028.7	1030.8	0.0	113.9	786.0	94.7	97.8	98.0
19/10/2015	17.3	20.7	26.8	57.0	78.7	94.0	0.0	4.6	0.0	1.7	9.4	17.3	27.6	1021.8	1024.9	1028.5	0.0	261.9	1071.0	92.1	96.7	98.0
20/10/2015	16.5	21.9	31.9	35.0	75.4	94.0	11.4	3.7	0.0	0.8	7.2	16.5	32.9	1015.9	1019.1	1022.1	0.0	208.4	968.0	86.0	95.0	98.0
21/10/2015	18.5	22.4	27.3	41.0	64.6	82.0	0.0	3.1	0.0	1.3	9.4	18.6	27.8	1011.9	1013.8	1015.8	0.0	140.3	876.0	87.4	97.0	100.0
22/10/2015	13.9	17.4	21.9	71.0	87.7	95.0	13.4	2.0	0.0	1.7	13.9	13.3	22.6	1010.8	1013.3	1019.4	0.0	113.7	1071.0	76.9	94.8	98.0
23/10/2015	11.9	14.8	17.9	61.0	81.1	95.0	0.8	1.6	0.0	0.8	8.9	12.1	18.0	1019.3	1022.9	1025.8	0.0	103.2	542.0	66.4	96.0	98.0
24/10/2015	9.6	16.1	23.4	56.0	79.6	98.0	0.3	3.9	0.0	1.6	9.4	9.6	23.9	1021.0	1023.6	1026.0	0.0	231.4	946.0	87.4	96.5	98.0
25/10/2015	12.1	19.1	28.1	47.0	75.9	96.0	0.0	4.1	0.0	1.3	8.0	12.1	28.8	1017.9	1020.5	1023.5	0.0	252.5	1117.0	93.9	96.4	98.0
26/10/2015	17.8	21.5	29.4	40.0	66.0	87.0	0.5	3.8	0.0	1.7	18.8	17.9	29.8	1014.7	1016.5	1020.8	0.0	175.5	964.0	60.2	95.2	98.0
27/10/2015	13.6	15.1	17.6	62.0	79.6	94.0	4.3	1.8	0.0	1.4	10.3	13.4	18.0	1020.8	1025.7	1027.9	0.0	98.3	468.0	72.8	95.0	98.0
28/10/2015	11.4	15.1	21.1	55.0	73.7	91.0	0.3	3.2	0.0	1.0	6.3	11.4	20.9	1023.1	1025.0	1027.2	0.0	186.9	1263.0	84.2	96.7	98.0
29/10/2015	10.5	15.8	22.2	49.0	73.1	95.0	0.0	4.0	0.0	1.3	8.0	10.5	22.0	1022.4	1024.1	1025.2	0.0	227.1	1112.0	78.9	95.9	98.0
30/10/2015	10.4	16.8	24.3	49.0	74.8	96.0	0.0	4.8	0.0	1.8	9.4	10.4	24.6	1021.0	1023.3	1025.2	0.0	282.8	1126.0	89.5	97.2	98.0
31/10/2015	13.6	18.3	23.9	54.0	79.1	94.0	0.0	3.2	0.0	1.4	8.9	13.6	24.5	1018.7	1020.8	1022.9	0.0	174.0	941.0	89.5	95.0	98.0
Monthly	9.6	19.2	37.5	10	72	99	49.7	118.1	0	1.3	18.8	9.6	35.2	1010.8	1024.1	1039.7	0	206.0	1263	44.7	96.4	100

2.4.2 Monthly Weather Charts








2.4.3 Monthly Windrose Plot

Frequency plot of the average wind speed and average direction over each 15 minute sampling period. Wind is considered to be calm when less than a 15 minute average of 1m/s.

00:15, 1 October 2015 – 23:45, 31 October 2015



The predominant winds were from the ENE, with most frequent, strongest winds from the WSW. The maximum wind speed was 18.8 m/s from the WSW.

Appendix 1

Laboratory Certificates



Environmental

CERTIFICATE OF ANALYSIS

Work Order	: EN1513710	Page	: 1 of 4
Client	: CARBON BASED ENVIRONMENTAL	Laboratory	: Environmental Division Newcastle
Contact	: MR COLIN DAVIES (cbased)	Contact	: Peter Keyte
Address	: 47 BOOMERANG ST CESSNOCK NSW, AUSTRALIA 2325	Address	: 5/585 Maitland Road Mayfield West NSW Australia 2304
E-mail	: cbased@bigpond.com	E-mail	: peter.keyte@alsglobal.com
Telephone	: +61 49904443	Telephone	: +61 2 4014 2500
Facsimile	: +61 02 49904442	Facsimile	: +61 2 4967 7382
Project	: Rocla Calga Dusts	QC Level	: NEPM 2013 Schedule B(3) and ALS QCS3 requirement
Order number	: ---	Date Samples Received	: 02-Nov-2015 11:50
C-O-C number	: ---	Date Analysis Commenced	: 03-Nov-2015
Sampler	: ---	Issue Date	: 05-Nov-2015 17:18
Site	:	No. of samples received	: 6
Quote number	: ---	No. of samples analysed	: 6

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results



NATA Accredited Laboratory 825

Accredited for compliance with
ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories

Position

Accreditation Category

Dianne Blane

Laboratory Coordinator (2IC)

Newcastle - Inorganics



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

Ø = ALS is not NATA accredited for these tests.

- Analysis as per AS3580.10.1-2003. Samples passed through a 1mm sieve prior to analysis. NATA accreditation does not apply for results reported in g/m².mth as sampling data was provided by the client.



Analytical Results

Sub-Matrix: **DEPOSITIONAL DUST**
 (Matrix: **AIR**)

Client sample ID

				CD1 02/10/15 - 02/11/15	CD2c 02/10/15 - 02/11/15	CD3 02/10/15 - 02/11/15	CD4 02/10/15 - 02/11/15	CD5 02/10/15 - 02/11/15
Client sampling date / time				[02-Nov-2015]	[02-Nov-2015]	[02-Nov-2015]	[02-Nov-2015]	[02-Nov-2015]
Compound	CAS Number	LOR	Unit	EN1513710-001	EN1513710-002	EN1513710-003	EN1513710-004	EN1513710-005
				Result	Result	Result	Result	Result
EA120: Ash Content								
Ash Content	---	0.1	g/m ² .month	1.2	0.5	0.4	0.2	0.3
Ash Content (mg)	---	1	mg	22	10	8	4	5
EA125: Combustible Matter								
Combustible Matter	---	0.1	g/m ² .month	0.4	0.4	0.4	0.2	0.2
Combustible Matter (mg)	---	1	mg	7	7	6	3	4
EA141: Total Insoluble Matter								
Total Insoluble Matter	---	0.1	g/m ² .month	1.6	0.9	0.8	0.4	0.5
Total Insoluble Matter (mg)	---	1	mg	29	17	14	7	9



Analytical Results

Sub-Matrix: **DEPOSITIONAL DUST**
(Matrix: **AIR**)

Client sample ID

				CD6	----	----	----	----
				02/10/15 - 02/11/15	----	----	----	----
				[02-Nov-2015]	----	----	----	----
				EN1513710-006	-----	-----	-----	-----
				Result	Result	Result	Result	Result
EA120: Ash Content								
Ash Content	---	0.1	g/m ² .month	0.3	---	---	---	---
Ash Content (mg)	---	1	mg	6	---	---	---	---
EA125: Combustible Matter								
Combustible Matter	---	0.1	g/m ² .month	0.2	---	---	---	---
Combustible Matter (mg)	---	1	mg	4	---	---	---	---
EA141: Total Insoluble Matter								
Total Insoluble Matter	---	0.1	g/m ² .month	0.5	---	---	---	---
Total Insoluble Matter (mg)	---	1	mg	10	---	---	---	---



ALS Environmental

CERTIFICATE OF ANALYSIS

Work Order	: ES1535084	Page	: 1 of 2
Amendment	: 1		
Client	: CARBON BASED ENVIRONMENTAL	Laboratory	: Environmental Division Sydney
Contact	: MR COLIN DAVIES (cbased)	Contact	:
Address	: 47 BOOMERANG ST CESSNOCK NSW, AUSTRALIA 2325	Address	: 277-289 Woodpark Road Smithfield NSW Australia 2164
E-mail	: cbased@bigpond.com	E-mail	:
Telephone	: +61 49904443	Telephone	: +61-2-8784 8555
Facsimile	: +61 02 49904442	Facsimile	: +61-2-8784 8500
Project	: ROCLA QUARRY	QC Level	: NEPM 2013 B3 & ALS QC Standard
Order number	: ---	Date Samples Received	: 02-Nov-2015 11:50
C-O-C number	: ---	Date Analysis Commenced	: 02-Nov-2015
Sampler	: ---	Issue Date	: 23-Nov-2015 14:05
Site	:		
Quote number	: ---	No. of samples received	: 3
		No. of samples analysed	: 3

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results



NATA Accredited Laboratory 825

Accredited for compliance with
ISO/IEC 17025.

Signatories

This document has been electronically signed by the authorized signatories indicated below. Electronic signing has been carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories	Position	Accreditation Category
Ankit Joshi	Inorganic Chemist	Sydney Inorganics
Merrin Avery	Supervisor - Inorganic	Newcastle - Inorganics



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Key : CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

Ø = ALS is not NATA accredited for these tests.

- Sampling time not provided. For operational reasons an assumed date/time (3pm on date of receipt) is used. Sample results may be affected if the analysis falls outside of actual holding time.
- TDS by method EA-015 may bias high for sample 2 due to the presence of fine particulate matter, which may pass through the prescribed GF/C paper.
- This report has been amended and re-released to allow the reporting of additional analytical data.

Analytical Results

Sub-Matrix: **WATER**
 (Matrix: **WATER**)

Sub-Matrix: WATER (Matrix: WATER)				Client sample ID		A	D	F	---	---
Client sampling date / time				[02-Nov-2015]		[02-Nov-2015]	[02-Nov-2015]	---	---	---
Compound	CAS Number	LOR	Unit	ES1535084-001		ES1535084-002	ES1535084-003	-----	-----	-----
				Result		Result	Result	Result	Result	Result
EA005: pH										
pH Value	---	0.01	pH Unit	5.37		5.97	4.93	---	---	---
EA010P: Conductivity by PC Titrator										
Electrical Conductivity @ 25°C	---	1	µS/cm	80		79	82	---	---	---
EA015: Total Dissolved Solids										
Total Dissolved Solids @180°C	---	10	mg/L	41		64	49	---	---	---
EA025: Suspended Solids										
Suspended Solids (SS)	---	5	mg/L	<5		22	38	---	---	---
EP020: Oil and Grease (O&G)										
Oil & Grease	---	5	mg/L	<5		<5	<5	---	---	---