



50 Junction Street, Nowra, NSW 2541

P: 4421 4583  
M: 0414 315 775

matthew@harwoodacoustics.com.au  
www.harwoodacoustics.com.au

ABN: 12 654 492 823

---

# Environmental Noise Compliance Assessment Bass Point Quarry 2022 – Quarter One

1 Bass Point Quarry Road,  
Shell Cove, NSW 2529

*Prepared for:-*

Hanson Construction Materials Pty Ltd  
Locked Bag 5260  
Parramatta NSW 2124

Attention: Ms Chelsea Flood

Reference: 2205018-R

*Prepared by:-*

Matthew Harwood MAAS  
26<sup>th</sup> August 2022



Environmental  
Acoustics

Occupational  
Acoustics

Architectural  
Acoustics

Transportation  
Acoustics



# Document Control Page

Revision	Author	Released By	Date
Draft	MH	MH	18/07/2022
Final	MH	MH	26/08/2022

Harwood Acoustics Pty. Ltd. was engaged by Hanson Construction Materials Pty Ltd to carry out quarterly noise compliance testing for its Bass Point Quarry at 1 Bass Point Quarry Road, Shell Cove, NSW. This assessment relates to Quarter One of 2022 and noise compliance testing was conducted in March 2022.

Accordingly, Harwood Acoustics Pty. Ltd. has prepared this report for the exclusive use of the Client identified on the title page. The report is prepared in accordance with the brief and scope of works agreed between the Client and Harwood Acoustics Pty. Ltd. and may not be suitable for use beyond that scope.

Harwood Acoustics Pty. Ltd. undertakes no duty nor accepts any responsibility to any third party who may rely upon this report.

The concepts and information within this report are the property of Harwood Acoustics Pty. Ltd. and the content herein should not be copied or reproduced, in whole or in part, without prior written consent.

Advice and recommendations provided in this report are in relation to acoustical issues only. No claims of expertise are made, and no liability is accepted, in relation to issues falling outside the field of acoustical consulting. These may include, but are not limited to, structural and waterproofing considerations, fire rating or thermal rating. Relevant authorities and / or experts should be consulted regarding areas other than acoustics.

## TABLE OF CONTENTS

1. INTRODUCTION AND SUMMARY.....	4
2. SITE AND DEVELOPMENT DESCRIPTION.....	5
2.1 Site Description .....	5
2.2 Development Description.....	7
3. NOISE CRITERIA.....	7
3.1 Acceptable Noise Limits .....	7
3.2 Noise Compliance Assessment Methodology .....	8
4. MODIFYING FACTOR ADJUSTMENTS.....	9
5. MEASURED NOISE LEVELS .....	9
6. CONCLUSION .....	15

## 1. INTRODUCTION AND SUMMARY

Hanson Construction Materials Pty Ltd (Hanson) currently operates the Bass Point Quarry at 1 Bass Point Quarry Road, Shell Cove, NSW (the Quarry).

The Quarry is located at the eastern end of Bass Point Quarry Road adjacent to the Killalea State Park. The nearest residences are located toward the north west and west in the village of Shell Cove as shown in Figure 1.

The Quarry operates 24 hours per day, seven days per week under Project Approval 08\_0143 issued by the Minister for Planning and Infrastructure on 28 January 2014 (the Approval).

It was previously a requirement of the Approval that monthly environmental noise compliance monitoring be undertaken. Since late 2017 environmental noise compliance monitoring became a quarterly requirement.

Schedule 3 of the Approval provides specific noise criteria that must be met at specifically identified receptor locations whilst the Quarry is operating. Appendix 6 of the Approval provides guidelines and requirements in relation to compliance noise monitoring methodology.

The specific acoustical parameters that are required to be assessed under the Project Approval are the  $L_{eq, 15 \text{ min}}$  parameter (being the energy average sound pressure level measured over a period of 15 minutes) and the  $L_{1,1 \text{ minute}}$  which is the noise level that is exceeded for 1% percent of 1 minute, which is essentially close to the maximum noise level).

This report addresses those requirements as well as the requirements of Hanson's Management Plan. Hanson's Management Plan requires several additional acoustical parameters to be recorded during noise compliance testing, being the:  $L_{max}$ ,  $L_{min}$ ,  $L_{10}$ ,  $L_{50}$ ,  $L_{90}$  and  $L_{99}$  in order to describe the ambient acoustical environment.

The author visited the site and all residential receptors on Friday 18 March 2022 to undertake attended noise compliance monitoring.

Noise measurements were taken in accordance with the requirements of the Approval and the Management Plan and the level of noise emission from the operation of the Quarry was found to be well below acceptable noise limits at all receptor locations as detailed in this Report.

The ambient acoustical environment at all receptor locations is dominated by either neighbourhood noise, passing traffic, insects, weather or surf noise from the ocean.

## **2. SITE AND DEVELOPMENT DESCRIPTION**

### **2.1 Site Description**

The Quarry is located adjacent to the Killalea State Park at the eastern end of Bass Point Quarry Road as shown in Figure 1 below.

The closest receptors to the site are in Shell Cove to the north west and west of the Quarry. Those identified in the Approval are receptors R4 through to R12 inclusive as detailed below.

All receptors are shown in Figure 1 and as follows:-

R4 – Sloop Avenue (cnr Cutter Parade)	R5 – Apollo Drive (cnr Clipper Avenue)
R6 – 1 Makaha Way	R7 – 44 Mystics Drive
R8 – 29 Hinchinbrook Drive	R9 – 23 Magnetic Ridge
R11 – 7 Joondalup Parkway	R12 – 3 Ranfurlie Parkway

Noise monitoring was also undertaken at an additional receptor – A1 – along Harbour Boulevard, in response to the substantial recent residential development in Shell Cove.



**Figure 1. Location Plan – Bass Point Quarry, Shell Cove, NSW**

*(source: Nearmap © 2019, image date 25/01/19 C/- Hanson Construction Materials Pty Ltd)*

## 2.2 Development Description

Hanson's Bass Point Quarry is an extractive industry (hard rock quarry) supplying a range of products for projects such as building railways, roads, bridges, dams, airports, etc.

Primary activities at the site include the extraction, crushing, sorting and despatching of construction aggregates and this involves the use of the following plant and equipment:-

- Operation of the primary crusher
- Final product load out (dump trucks)<sup>1</sup>
- Load and haul pit operations (front end loader and two dump trucks)<sup>2</sup>
- Wash plant operations (generator, pump, wash plant and loader)<sup>4</sup>
- Operation of the secondary crusher
- Operation of the tertiary crusher
- Sales operations (loading product into road trucks for dispatch – loaders & trucks)<sup>3</sup>

Notes:-

1. CAT 777 and Komatsu 325 dump trucks
2. Komatsu WA 800 loader and CAT 777 dump trucks
3. Komatsu WA 500 loader, Volvo L 250 loader and various trucks, and
4. CAT 980 loader.

The above listed plant and machinery typically operates up until approximately 10 pm and constitutes full operation of the site. Normally, from approximately 10 pm the majority of operations cease with the exception of the secondary crushing plant and despatch loaders and trucks. On occasion, due to increased demand for aggregates, operating hours are regularly extended.

## 3. NOISE CRITERIA

Project specific noise limits and compliance testing conditions and methodology are derived from the Approval, and are as follows.

### 3.1 Acceptable Noise Limits

Schedule 3, Clause 3, Table 2 of the Approval sets noise criteria for each receptor location. Table 2 of the Approval is replicated in Table 1 below.

**Table 1 Noise Criteria** (Project Approval, Schedule 3 - Table 2)

Location	Day / Evening	Night	
	(L <sub>Aeq</sub> , 15 min)	(L <sub>Aeq</sub> , 15 min)	(LA <sub>1</sub> , 1 min)
R4	44	44	54
R5	45	45	55
R6	42	42	52
R7	41	41	51
R8	35	35	45
R9	35	35	45
R11	45	45	55
R12	45	45	55
Any residential property within the Shell Harbour Marina Precinct	48	48	58
Shell Cove Primary School (when in use)	L <sub>Aeq</sub> , 1 hour 40 (internal)	Not Applicable	

*“Notes:*

*Noise generated by the project is to be measured in accordance with the relevant requirements of the NSW Industrial Noise Policy. Appendix 6 sets out the meteorological conditions under which these criteria apply, and the requirements for evaluating compliance with these criteria.*

*However, these criteria do not apply if the Proponent has a written agreement with the relevant landowner to exceed the criteria, and the Proponent has advised the Department in writing of the terms of this agreement.”*

### **3.2 Noise Compliance Assessment Methodology**

Appendix 6 of the Approval provides conditions and assessment methodology that is to be adhered to during noise compliance monitoring, and states:-

#### *“Applicable Meteorological Conditions*

*1. The noise criteria in Table 1 of the conditions are to apply under all meteorological conditions except the following:*

- (a) during periods of rain or hail;*
- (b) average wind speed at microphone height exceeds 5m/s;*
- (c) wind speeds greater than 3 m/s measured at 10 m above ground level; or*
- (d) temperature inversion conditions greater than 3°C/100 m.*

#### *Determination of Meteorological Conditions*

*2. Except for wind speed at microphone height, the data to be used for determining meteorological conditions shall be that recorded by the meteorological station on or in the vicinity of the site.*

#### *Compliance Monitoring*

*3. Unless otherwise agreed, this monitoring is to be carried out in accordance with the relevant requirements for reviewing performance set out in the NSW Industrial Noise Policy (as amended from time to time), in particular the requirements relating to:*

- (a) monitoring locations for the collection of representative noise data;*
- (b) meteorological conditions during which collection of noise data is not appropriate;*
- (c) equipment used to collect noise data, and conformity with Australian Standards relevant to such equipment; and*
- (d) modifications to noise data collected including for the exclusion of extraneous noise and/or penalties for modifying factors apart from adjustments for duration.”*

### **3.3 Hanson Construction Materials’ Management Plan**

Hanson operates its Bass Point Quarry under a Management Plan, which in relation to acoustical compliance testing, in Section 4.2, states:-

*Operator attended noise measurements and recordings will be conducted to quantify the intrusive noise emissions from quarrying and processing operations as well as the overall level of ambient noise.*

*The operator will quantify and characterise the maximum ( $L_{Amax}$ ) and the average ( $L_{Aeq(15\text{ minute})}$ ) intrusive noise level from quarrying and processing operations over a*



*15 minute measurement period. In addition, the operator must quantify and characterise the overall levels of ambient noise (i.e.  $L_{Amax}$ ,  $L_{A1}$ ,  $L_{A10}$ ,  $L_{A50}$ ,  $L_{A90}$ ,  $L_{A99}$ ,  $L_{Amin}$ ) over the 15 minute measurement interval.*

#### **4. MODIFYING FACTOR ADJUSTMENTS**

Where a noise source contains certain characteristics, such as tonality, intermittency, irregularity or dominant low-frequency content, there is evidence to suggest that it can cause greater annoyance than other noise at the same noise level. On the other hand, some sources may cause less annoyance where only a single event occurs for a limited duration.

Fact Sheet C of the Noise Policy for Industry 2017 outlines the correction factors to be applied to the source noise level at the receiver before comparison with the project noise trigger levels, to account for the additional annoyance caused by these modifying factors.

The modifying factor corrections should be applied having regard to:

- the contribution noise level from the premises when assessed/measured at a receiver location, and
- the nature of the noise source and its characteristics (as set out in this fact sheet).

Table C1 sets out the corrections to be applied. The corrections specified for tonal, intermittent and low-frequency noise are to be added to the measured or predicted noise levels at the receiver before comparison with the project noise trigger levels. The adjustments for duration are to be applied to the criterion.

Table C1 of Fact Sheet C is replicated in the attached Appendix B.

In this instance the measured noise levels at all receptor locations during the evening and night time periods did not display characteristics requiring modifying factor adjustments.

#### **5. MEASURED NOISE LEVELS**

##### **5.1 Noise Measurement Results**

The author visited the Quarry and each of the receptor locations to carry out attended noise measurements during the evening and night time periods on Friday 18 March 2022. Noise measurements were undertaken at each receptor location shown in Figure 1, between the hours of approximately 7.00 pm and 10.45 pm. During the noise survey, the weather was warm with temperatures of approximately 23 to 25 degrees Celsius and clear skies. Conditions were calm with wind speeds below 5 m/s at microphone height throughout the majority of the survey. At locations closer to the water, surf noise was clearly dominant. Care was taken to avoid taking noise measurements, or pausing the sound level meter during wind gusts when necessary and as far as was reasonably practicable as is often the case in Shell Cove, particularly near Killalea State Park.

The Quarry was in full operation throughout the entire noise survey. All measurements were also paused as trucks passed along the Haul Road, whenever this was practicable.

All measurements were carried out in accordance with Australian Standard AS 1055-1997 'Acoustics - Description and measurement of environmental noise' and the instrumentation used during the noise survey is shown in the attached Appendix A.

The results of the survey are shown in Tables 2, 3 and 4 below, where:-

- Table 2 shows the measured and predicted  $L_{eq, 15 \text{ minute}}$  noise levels for assessment against the Intrusiveness criteria as required by the Project Approval,
- Table 3 shows the measured and predicted  $L_{1, 1 \text{ minute}}$  noise levels for assessment against the Sleep Disturbance criteria as required by the Project Approval, and
- Table 4 shows the measurement parameters required to be recorded under the Management Plan.

**Table 2 Measured & Estimated  $L_{eq, 15 \text{ minute}}$  Noise Levels – 18 March 2022**

Location / Time / Description	Noise Level (dBA)				Complies
	Measured Noise Level	Typical Extraneous Noise Sound Pressure Level	Estimated Quarry Noise Level $L_{eq, 15 \text{ minute}}$	Acceptable Noise Limit $L_{eq, 15 \text{ minute}}$ Day, Evening & Night	
R4 – Sloop Avenue (9.30 – 9.45 pm) Quarry not audible	39	Traffic and Neighbourhood noise 45 - 48 Lulls 39 / 40	<40	44	Yes
R5 – Apollo Drive (9.10 to 9.25 pm) Quarry not audible	43	Water treatment 43 Lulls 40	<40	45	Yes
R6 – 1 Makaha Way (7.50 to 8.05 pm) Quarry not audible	42	Neighbourhood noise 40 - 45 Lulls 38	<38	42	Yes
R7 – 44 Mystics Drive (8.08 to 8.23 pm) Quarry not audible	42	Traffic 42 – 45 Lulls 34	<35	41	Yes
R8 – 29 Hinchinbrook Drive (8.30 to 8.45 pm)	39	Distant traffic > 40 Lulls 35	<35	35	Yes
R9 – 23 Magnetic Ridge (8.50 to 9.05 pm) Quarry not audible	36	Lulls 34	<34	35	Yes
R11 – 7 Joondalup Parkway (7.20 pm to 7.35 pm) Quarry faintly audible	41	Insects & Traffic 39 / 40 Lulls 37 / 38	<37	45	Yes
R12 – 3 Ranfurlie Parkway (9.55 to 10.10 pm) Quarry faintly audible	32	Lulls <30	<30	45	Yes
A1 – Harbour Boulevard (6.55 to 7.10) Quarry not audible	53	Traffic 50 – 55 Surf & lulls 47	<47	48	Yes

**Nearest residence location and discussion**

\* Noise measurements were taken near to the closest residential receptor to the quarry, as indicated in Figure 1 (A1) which is the site of further residential expansion and land release.

It is worth noting that the development along Harbour Boulevard is rapidly moving south east toward the quarry, such that there are new dwellings this quarter compared to last quarter.

In each instance the measurement location for this receptor has been taken to be the newest, closest, property to the Quarry. In line with other receptors, it seems reasonable that a fixed location for Harbour Boulevard assessment may be identified.

There was a hum noticeable at this location which may be the primary crusher operating, however the noise levels are dominated by passing traffic at this location.

This location is within the new Shell Harbour Marina Precinct and the appropriate acceptable noise limits for this area are derived from the Approval, which are shown in Table 2 in schedule 3 of the Project Approval, which are reiterated in Table 1 of this report.

**Table 3 Measured & Calculated L<sub>1, 1 minute</sub> Noise Levels – 18 March 2022**

Location / Description	Noise Level (dBA)				Complies
	Measured Noise Level L <sub>1, 1 minute</sub>	Typical Extraneous Noise Sound Pressure Level	Estimated Quarry Noise Level L <sub>1, 1 minute</sub>	Acceptable Noise Limit L <sub>1, 1 minute</sub> at night	
R4 – Sloop Avenue (9.46 pm) not audible	43	Distant traffic	<43	54	Yes
R5 – Apollo Drive (9.26 pm) not audible	46	Water treatment plant	<46	55	Yes
R6 – 1 Makaha Way (10.30 pm) not audible	47	traffic	<47	52	Yes
R7 – 44 Mystics Drive (10.33 pm) not audible	44	neighbourhood	<39	51	Yes
R8 – 29 Hinchinbrook Drive (10.25 pm) not audible	39	Distant traffic	<39	45	Yes
R9 – 23 Magnetic Ridge (10.20 pm) not audible	37	-	<37	45	Yes
R11 – 7 Joondalup Parkway (10.14 pm) faintly audible	42	Quarry*	<42	55	Yes
R12 – 3 Ranfurlie Parkway (10.11 pm) faintly audible	38	Quarry*	<38	55	Yes
A1 – Harbour Boulevard (10.38) not audible	49	Quarry (?) / Surf noise	<49	58	Yes

\* At no time was the quarry audible during the  $L_{1, 1 \text{ minute}}$  measurements after 10 pm with the exception of receptor R12, where a hum could be heard. Even in this instance it is likely that the measured noise levels are affected, if not dominated, by extraneous noise.

All other measured noise levels in Table 3 are dominated by extraneous noise.

Table 4 below shows the measured noise levels at each receptor location during the 15 minute measurements including each of the acoustical parameters prescribed in the Management Plan.

**Table 4 Measured Noise Levels – 18 March 2022 (Additional Parameters)**

Location / Description	Noise Level (dBA) $L_x$ , 15 minute							
	$L_{\text{max}}$	$L_{\text{eq}}$	$L_1$	$L_{10}$	$L_{50}$	$L_{90}$	$L_{99}$	$L_{\text{min}}$
R4 – Sloop Avenue (9.30 – 9.45 pm)	51	39	42	41	40	35	33	31
R5 – Apollo Drive (9.10 to 9.25 pm)	62	43	53	46	39	36	36	33
R6 – 1 Makaha Way (7.50 to 8.05 pm)	66	42	52	43	39	37	37	36
R7 – 44 Mystics Drive (8.08 to 8.23 pm)	74	42	52	40	36	36	36	35
R8 – 29 Hinchinbrook Drive (8.30 to 8.45 pm)	59	39	50	39	37	36	35	34
R9 – 23 Magnetic Ridge (8.50 to 9.05 pm)	54	36	38	37	36	35	35	33
R11 – 7 Joondalup Parkway (7.20 pm to 7.35 pm)	57	41	49	43	39	38	37	36
R12 – 3 Ranfurlie Parkway (9.55 to 10.10 pm)	40	32	38	33	31	30	30	29
A1 – Harbour Boulevard (6.55 to 7.10)	73	53	67	51	49	43	41	38

## 5.2 Noise Assessment and Discussion

### Tables 2 and 3 – Assessment of $L_{\text{eq}}$ 15 minute and $L_1$ , 1 minute noise levels.

The contribution of Quarry noise emission to the measured levels in Table 2 has been estimated based on observations of the sound pressure level during lulls in extraneous and ambient noise, whilst the Quarry was operating, and the subjective audibility of the Quarry. In each instance these estimated levels are still considered to be conservatively high.

Extraneous noise levels are mostly excluded from Table 3 as the measured  $L_{1, 1 \text{ minute}}$  noise level is so far below the acceptable noise limit at each location, in every instance, irrespective of the contribution of Quarry noise.

During this particular survey, at no time was noise emission from the quarry audible at any receptor location with the exception of locations R11 and R12 where noise from the quarry was audible. Sometimes as a faint, almost indistinguishable hum and sometimes clearly.

As an example, at 7.20 pm at R11 (Joondalup Parkway), a distant hum was faintly audible on occasion amid insect noise and distant road traffic from Shellharbour Road. After 10 pm however at R12 (Ranfurlie) and again at R11, noise from the primary crusher and broadband reversing alarms were noticeable in contrast to the significantly lower ambient and extraneous noise levels. Notwithstanding this, the measured noise levels which included quarry noise emission were well below the allowable noise limit in each instance.

Noise measurements are dominated by extraneous noise and consequently the contribution of noise from the Quarry to the actual measured noise levels is likely to be lower still, often considerably, than those levels estimated in Tables 2 and 3.

Compliance with the acceptable intrusiveness noise limits during the full operation of the quarry in the evening prior to 10 pm, also demonstrates compliance during the night time, with the same intrusive noise limits during either the same or reduced operations as the night goes on.

Measurements and predictions therefore show that the level of noise emission from the operation of the Quarry during the noise survey was below the Project Approval noise limits at all receptor locations, at all times.

*Table 4 – Assessment of additional acoustical parameters.*

During this particular survey on Friday 18 March 2022, extraneous noise consisted of distant traffic on Shellharbour Road, significant (on occasion) neighbourhood noise as well as passing cars, insects and surf noise. Noise emission from the marina precinct was not subjectively noticeable during this survey. Noise levels at receptor A1 along Harbour Boulevard were dominated exclusively by surf noise and passing traffic, where in the past, noise from the marina precinct has been influential at this location.

Noise emission from the water treatment plant (sewage plant) was dominant at receptor R5 in Apollo Avenue which is not always the case.

Table 4 shows the measured noise levels for each of the parameters required to be assessed under the Management Plan.

The noise levels represent various ambient and extraneous noise events, for example:-

- $L_{max}$  noise levels are dominated by passing traffic, neighbourhood noise such as garage doors closing, bin lids closing, dogs barking, etc,
- $L_{eq}$  noise levels are the energy average noise levels measured and provided in Table 2 and used to predict the contribution (if at all) of Quarry noise,
- $L_1$  noise levels are affected by neighbourhood noise similar to that which dominates the maximum levels listed above. The  $L_{1, 15 \text{ minute}}$  noise levels are different to the  $L_{1, 1 \text{ minute}}$  noise levels provided in Table 3, as these are assessed over a different duration – for example the  $L_{1, 1 \text{ minute}}$  noise level is essentially the noise level that is exceeded for 1 % of 60 seconds (i.e. 0.6 seconds), whereas the  $L_{1, 15 \text{ minute}}$  is the noise level that is exceeded for 1 % of 15 minutes (i.e. 9 seconds),

- **L<sub>10</sub>** noise levels are typically dominated by passing and distant road traffic, depending upon the measurement location and activity on local roads at the time of the measurements as well as insects in the summer months,
- **L<sub>50</sub>** noise levels represent the statistically average level of measured noise, being the median value of the fluctuating noise levels over the measurement period (15 minutes in this instance). If quarry activity was a contributing factor to the acoustical environment at any receptor, then this would be reflected in the L<sub>50</sub> noise level. It can be seen that the L<sub>50</sub> noise level is often also below the L<sub>eq</sub> noise limits at all receptors even if it did contain contributions of Quarry noise,
- **L<sub>90</sub>** noise levels represent the “background” noise level, being the noise level that is exceeded for 90 % of the time (i.e. the quietest 10 % of noise in 15 minutes). In Shell Cove, the background noise level is dominated by insects, surf noise or the rustling of wind in trees, depending on the measurement location and time of year. It is perhaps useful in describing quarry noise contributions if it is the case that the quarry was operating at a steady state for a minimum period of 15 minutes. For example, if the primary crusher was operating for at least 15 minutes and the noise level from the crusher did not vary significantly over that 15 minute period, then the measured L<sub>90</sub> noise level could be considered representative of quarry noise emission. Again, if this were the case on any occasion, then it can be seen that the L<sub>90, 15 minute</sub> noise levels are at or below the noise limits with the exception of receptor R8 where the measured L<sub>90 (15 minute)</sub> noise level was 36 dBA and the noise limit is 35 dBA. The L<sub>90, 15 minute</sub> noise level at this receptor during this particular noise survey however is dominated by distant traffic and neighbourhood hum and not quarry noise, as evidenced by observations of the sound pressure level, inaudibility and subjective assessment,
- **L<sub>99</sub>** noise levels are essentially the opposite to the L<sub>1</sub> noise level and represent the noise level that is exceeded for 99 % of the time (i.e. the quietest 1 % of noise in 15 minutes) and is similar to the minimum noise level.
- **L<sub>min</sub>** is the minimum noise level during the measurement period and represents the quietest noise level in the absence of any extraneous noise.

## 6. CONCLUSION

Environmental Noise Compliance testing has been undertaken at Hanson's Bass Point Quarry in accordance with the requirements of the Project Approval 08\_0143.

The level of noise emission from the Quarry was found to be below the Project Approval noise limits at all times, at all receptor locations.



**Matthew Harwood**, MAAS

Principal Acoustical Consultant

Attachments:-

Important Note

Appendix A – Noise Survey Instrumentation

Appendix B – Modifying Factor Corrections (EPA NPI 2017)

**Important Note**

*All products and materials suggested by Harwood Acoustics Pty Ltd are selected for their acoustical properties only.*

*Recommendations made in this report are intended to resolve acoustical problems only, therefore all other properties such as aesthetics, air flows, chemical, corrosion, combustion, construction details, decomposition, expansion, fire rating, fumes, grout or tile cracking, loading, shrinkage, smoke, ventilation etc. are outside Harwood Acoustic's fields of expertise and **must** be checked with the supplier or suitably qualified specialist before purchase.*

**Disclaimer**

*While every reasonable effort has been made to ensure that this document is correct at the time of printing, Harwood Acoustics Pty Ltd, their Associates, Subcontractors and employees make no representation, undertake no duty and accept no responsibility to any third party who use or rely upon this document or the information contained in it. No guarantees are either expressed or implied.*

*This report has been prepared solely for use by the Client identified on the title page as per our agreement for providing noise assessment services; and is entitled to rely upon the findings in the report within the scope of work described in this report.*

*Although all due care has been taken in the preparation of this report, no warranty is given, nor liability accepted (except that required by law) in relation to the information contained within this document.*

*This report and information therein cannot be relied on or used by any third party. Any representation, statement, opinion or advice, expressed or implied in this report is made in good faith but on the basis that Harwood Acoustics Pty Ltd are not liable (whether by reason of negligence, lack of care or otherwise) to any person for any damage or loss whatsoever which has occurred or may occur in relation to that person taking or not taking (as the case may be) action in any respect of any representation, statement, or advice referred to above.*

*No responsibility is accepted for the use of any part of the report in any other context or for any other purpose.*

*Opinions and judgements expressed herein, which are based on our understanding and interpretation of current regulatory standards, should not be construed as legal opinions.*

*Harwood Acoustics Pty Ltd reserves all copyright of intellectual property in any or all of Harwood Acoustics Pty Ltd documents. No permission, license or authority is granted by Harwood Acoustics Pty Ltd to any person or organisation to use any of Harwood Acoustics Pty Ltd documents for any purpose without the written consent of Harwood Acoustics Pty Ltd.*



<b>Noise Survey Instrumentation</b>	<b>Appendix A</b>
-------------------------------------	-------------------

The instrumentation used during the noise survey consisted of the following:-

<b>Description</b>	<b>Model No.</b>	<b>Serial No.</b>
Bruel and Kjaer Sound Level Meter	2250	3009198
Bruel and Kjaer Acoustical Calibrator	4321	3003242

The sound level meter conforms to Australian Standards AS IEC 61672.1-2004 : 'Electroacoustics - Sound level meters – Specifications' as a Class 1 precision sound level meter.

The calibration of the meter was checked before and after the measurement period. No significant system drift occurred over the measurement period. The sound level meter and calibrator have been checked, adjusted and aligned to conform to the factory specifications and issued with conformance certificates.

<b>Modifying Factor Corrections (EPA 2017)</b>	<b>Appendix B</b>
--	-------------------

**Table C1 Modifying Factor Corrections** (from Table C.1 of the NSW Noise Policy for Industry 2017)

Factor	Assessment/ Measurement	When to Apply	Correction	Comments
Tonal Noise	One-third octave band analysis using the objective method for assessing the audibility of tones in noise – simplified method ( <i>ISO1996.2-2007 – Annex D</i> ).	Level of one-third octave band exceeds the level of the adjacent bands on both sides by: <ul style="list-style-type: none"> <li>• 5 dB or more if the centre frequency of the band containing the tone is in the range 500–10,000 Hz</li> <li>• 8 dB or more if the centre frequency of the band containing the tone is in the range 160–400 Hz</li> <li>• 15 dB or more if the centre frequency of the band containing the tone is in the range 25–125 Hz.</li> </ul>	5 dB	Third octave measurements should be undertaken using unweighted or Z-weighted measurements. <b>Note:</b> Narrow-band analysis using the reference method in <i>ISO1996-2:2007, Annex C</i> may be required by the consent/regulatory authority where it appears that a tone is not being adequately identified, e.g. where it appears that the tonal energy is at or close to the third octave band limits of contiguous bands.
Low Frequency Noise	Measurement of source contribution C-weighted and A-weighted level and one-third octave measurements in the range 10–160 Hz	Measure/assess source contribution C- and A-weighted Leq,T levels over same time period. Correction to be applied where the C minus A level is 15 dB or more and: <ul style="list-style-type: none"> <li>• where any of the one-third octave noise levels in Table C2 are exceeded by up to and including 5 dB and cannot be mitigated, a 2 dB(A) positive adjustment to measured/predicted A-weighted levels applies for the evening/night period</li> <li>• where any of the one-third octave noise levels in Table C2 are exceeded by more than 5 dB and cannot be mitigated, a 5-dB(A) positive adjustment to measured/predicted A-weighted levels applies for the evening/night period and a 2-dB(A) positive adjustment applies for the daytime period.</li> </ul>	2 or 5 dB	A difference of 15 dB or more between C- and A-weighted measurements identifies the potential for an unbalance spectrum and potential increased annoyance. The values in Table C2 are derived from Moorhouse (2011) for DEFRA fluctuating low-frequency noise criteria with corrections to reflect external assessment locations.

**Table C1 Modifying Factor Corrections** (from Table C.1 of the NSW Noise Policy for Industry 2017) *Cont...*

Factor	Assessment/ Measurement	When to Apply	Correction	Comments
Intermittent Noise	Subjectively Assessed but should be assisted with measurement to gauge the extent of change in noise level.	The source noise heard at the receiver varies by more than 5 dB(A) and the intermittent nature of the noise is clearly audible.	5 dB	Adjustment to be applied for <b>night-time only</b> .
Duration	Single-event noise duration may range from 1.5 m to 2.5 h	One event in any 24-hour period	0 to -20dBA	The acceptable noise trigger level may be increased by an adjustment depending on duration of noise (see Table C.3)
Maximum adjustment	Refer to individual modifying factors	Where two or more modifying factors are indicated	Maximum correction of 10 dBA <sup>2</sup> (excluding duration correction)	

**Notes:**

1. Corrections to be added to the measured or predicted levels, except in the case of duration where the adjustment is to be made to the criterion.
2. Where a source emits tonal and low-frequency noise, only one 5-dB correction should be applied if the tone is in the low-frequency range, that is, at or below 160 Hz.
3. Where narrow-band analysis using the reference method is required, as outlined in column 5, the correction will be determined by the ISO1996-2:2007 standard.